



Sigefi Efenergy Cofitroller

3.0- 120kW Single Phase

- EMS inside for precise control
- On & off-grid compatibility
- Up to 4 MPP. trackers
- DC/AC ratio up to 2
- Multi-source black start
- IP66 system protection rating

Sigefi Efnergy Cofitroller 3.0-12.0kW Single Phase ¹

SigenStor EC	3.0 SP	3.6 SP	4.0 SP	4.6 SP	5.0 SP	6.0 SP	8.0 SP	10.0 SP	12.0 SP	Units	
DC Input (from PV)											
Max. PV power	6000	7360	8000	9200	10000	12000	16000	20000	24000	W	
Max. DC input voltage					600					V	
Nominal DC input voltage					350					V	
Start-up voltage					100					V	
MPPT voltage range					50 ~ 550						V
Number of MPP. trackers					2		3	4	4		
Number of PV strings per MPPT					1						
Max. input current per MPPT					16						A
Max. short-circuit current per MPPT					20						A
AC Output (on-grid)											
Nominal output power	3000	3680	4000	4600	5000	6000	8000	10000	12000	W	
Max. output apparent power	3300	3680	4400	5000	5500	6600	8800	11000	12000	VA	
Nominal output current	13.6	16.0	18.2	20.9	22.7	27.3	36.4	45.5	54.6	A	
Max. output current	15.0	16.0	20.0	22.7	25.0	30.0	40.0	50.0	54.6	A	
Nominal output voltage					220 / 230 / 240		220 / 230				V
Nominal grid frequency					50 / 60						Hz
Power factor					0.8 leading ~ 0.8 lagging						
Total current harmonic distortion					THDi < 2%						
Efficiency											
Max. efficiency	98.0%	98.0%	98.0%	98.0%	98.0%	98.0%	97.6%	97.6%	97.6%		
European efficiency	97.0%	97.1%	97.2%	97.3%	97.4%	97.4%	97.0%	97.0%	97.0%		
AC Output (backup)											
Peak output power (10 seconds)	4500	5520	6000	6900	7500	9000	12000	15000	15000	W	
Nominal output voltage					220 / 230 / 240		220 / 230				V
Nominal output frequency					50 / 60						Hz
Power factor					0.8 leading ~ 0.8 lagging						
Total voltage harmonic distortion					THDv < 2%						
Disruption time of backup switch ²					0						ms
Battery Connection											
Battery module models					SigenStor BAT 5.0 / 8.0						
Number of modules per controller					1~6						pcs
Battery module voltage range					300 ~ 600						V
Protection											
Safety protection feature	DC reverse polarity protection, Insulation monitoring, Residual current monitoring, Arc fault circuit interrupter ³ , AC overcurrent/overvoltage/short-circuit protection. Type II DC/AC surge protection, Anti-islanding protection										
General Data											
Dimensions (W / H / D)					700 / 300 / 245		700 / 300 / 260				m m
Weight					18		36				kg
Storage temperature range					-40 ~ 70						°C
Operating temperature range					-30 ~ 60						°C
Relative humidity range					0% ~ 95%						
Max. operating altitude					4000						m
Cooling					Natural convection		Smart air cooling				
System ingress protection rating					IP66						
Communication	WLAN / Fast Ethernet / RS485 / Sigen Co mm Mod (4G/3G/2G)										
Standard Compliance											
Standard ⁴	IEC/EN 62109-1, IEC/EN 62109-2, IEC/EN 62477, IEC/EN 61000-6-1, IEC/EN 61000-6-2										

Safety protection feature

DC reverse polarity protection, Insulation monitoring, Residual current monitoring, Arc fault circuit interrupter ³, AC overcurrent/overvoltage/short-circuit protection.
Type II DC/AC surge protection, Anti-islanding protection

General Data

Dimensions (W / H / D)					700 / 300 / 245		700 / 300 / 260				m m
Weight					18		36				kg
Storage temperature range					-40 ~ 70						°C
Operating temperature range					-30 ~ 60						°C
Relative humidity range					0% ~ 95%						
Max. operating altitude					4000						m
Cooling					Natural convection		Smart air cooling				
System ingress protection rating					IP66						
Communication	WLAN / Fast Ethernet / RS485 / Sigen Co mm Mod (4G/3G/2G)										

Standard Compliance

Standard ⁴ IEC/EN 62109-1, IEC/EN 62109-2, IEC/EN 62477, IEC/EN 61000-6-1, IEC/EN 61000-6-2

1. Sigen Energy Controller 8.0-12.0 kW Single Phase is only available in specific regions. Please contact Sigenergy or local distributors for details.
2. This refers to the load-side disruption time, to achieve this functionality Sigen Energy Gateway needs to be used together with Sigen Energy Controller and Sigen Battery. Test conditions: In the open-circuit state of the power grid, the nominal power of the Sigen Energy Controller is higher than the total power of the home loads.
3. This is an optional feature only supported in certain models, please contact Sigenergy for more information.
4. For all standards refer to the certificates category on the Sigenergy website.

Disclaimer: The information in this file is provided on an "as is" basis. To the fullest extent permitted by law, Sigenergy Technology Co., Ltd. excludes all representations and warranties relating to this file and its contents or which is or may be provided by any affiliates or any other third party, including in relation to any inaccuracies or omissions in this file.